

SRF RETROFIT FIRESLEEVE



WHAT IS IT?

SRF Firesleeve is manufactured from 'E' glass fibre yarn knitted into a sleeve and coated with high-grade silicone elastomer rubber.

APPLICATIONS

Protects wires, cables and hoses from high ambient temperatures.

Shields personnel from burns on hot pipes, steam lines and hot boxes.

Reduces energy loss by retaining heat within pipework.

Resistant to oils, hydraulic fluids, fuels, acids and alkalis.

STANDARD FORMAT

Inside diameter:	4mm to 203mm
Method of supply:	15 m coils
Hook & Loop size:	16 mm

RETROFIT HOOK & LOOP

Designed for installation without the need to remove existing wires, cables or hoses.

Fire retardant hook & loop fastener, stitched with glass thread — strong and durable.

AVAILABLE COLOURS

QUICK FACTS

Standard colour	Red Oxide
Continuous operating temp	260°C (500°F)
Molten splash resistance	Outstanding
Flame resistance	Very good
Abrasion resistance	Very good
Flexibility	Outstanding
Water & oil resistance	Outstanding
Wall thickness	4 mm ± 0.5 mm
Avg. dielectric strength	30 kV+

COMPLIANCE & CERTIFICATIONS

- ✔ Complies with EN 45545-2
- ✔ Tested to ISO 11925-2
- ✔ Meets requirement for IEC 60695-11-10
- ✔ Classified HB and V0
- ✔ Meets UL94 V0, V1, V2 rating requirements
- ✔ Made in Britain

CONTINUOUS
260°C
500°F

MOLTEN SPLASH
1200°C
2192°F