

SRF Retrofit Firesleeve - Heavy Industry Edition

Molten Splash Resistant · Made in Britain

FOUNDRIES - STEEL WORKS - SMELTING PLANTS - GLASS & CERAMICS

SRF RETROFIT FIRESLEEVE



WHAT IS IT?

SRF Firesleeve is manufactured from 'E' glass fibre yarn, coated with high-grade silicone elastomer rubber with hook & loop closure.

HEAVY INDUSTRY APPLICATIONS

- In-situ hydraulic hose upgrade on foundry plant
- Retrofit protection on ladle & crane hose runs
- Steel works hose protection without shutdown
- Kiln & furnace cable retrofit installations
- Plant maintenance without hose disconnection
- Emergency repair on live production equipment

STANDARD FORMAT

Inside diameter: **4 mm to 203 mm**
Method of supply: **15 m coils**
Hook & Loop size: **16 mm**

RETROFIT & PLANT MAINTENANCE

Installs without removing hoses or cables — critical for live plant where shutdown is costly.
Fire retardant hook & loop, glass-stitched.

AVAILABLE COLOURS



QUICK FACTS

Standard colour	Red Oxide
Continuous operating temp	260 C (500 F)
Molten splash resistance	Outstanding
Flame resistance	Very good
Abrasion resistance	Very good
Chemical resistance	Outstanding
Oil & fluid resistance	Outstanding
Avg. dielectric strength	30 kV+
Wall thickness	4 mm +/- 0.5 mm

COMPLIANCE & CERTIFICATIONS

✓ EN 45545-2	Fire protection standard
✓ ISO 11925-2	Ignitability of products
✓ IEC 60695-11-10	Classified HB and V0
✓ UL94 V0/V1/V2	UL flammability rating
✓ MSHA Certified	Mine Safety & Health Admin.
✓ Made in Britain	Manufactured in Burnley, UK

CONTINUOUS

260C

500F

MOLTEN SPLASH

1200C

2192F

SiO₂ BARRIER

Ceramic

on flame contact