

ENGINE ROOMS - OFFSHORE PLATFORMS - NAVAL & COMMERCIAL VESSELS

SRF FIRESLEEVE TAPE



WHAT IS IT?

SRF Firesleeve Tape is woven from 'E' glass fibre yarn and coated with high-grade silicone elastomer rubber. Available in 5 widths.

MARINE APPLICATIONS

- Terminating & sealing firesleeve at hose ends
- Wrapping hydraulic fittings & manifold ports
- Fuel line joint & elbow sealing
- Electrical conduit entry point sealing
- Offshore deck hose lap-joint protection
- Engine room cable bundle wrapping

STANDARD FORMAT

Widths available: **25, 50, 75, 100, 125 mm**
Method of supply: **30 m coils / cut lengths**

MARINE APPLICATION TIPS

Apply with 50% overlap for full coverage.
Use to terminate & seal firesleeve ends on engine room hoses without removal.
Salt & oil resistant — no degradation.

QUICK FACTS

Standard colour	Red Oxide
Continuous operating temp	250 C (482 F)
Molten splash resistance	Outstanding
Flame resistance	Very good
Salt & water resistance	Outstanding
Chemical resistance	Outstanding
UV & weather resistance	Outstanding
Avg. dielectric strength	30 kV+
Wall thickness	3 - 4 mm

MARINE COMPLIANCE & STANDARDS

ISO 11925-2	Ignitability of products
IEC 60695-11-10	Classified HB and V0
UL94 V0 / V1 / V2	UL flammability rating
EN 45545-2	Fire protection standard
MSHA Certified	Mine Safety & Health Admin.
Made in Britain	Manufactured in Burnley, UK

CONTINUOUS 250C 482F	MOLTEN SPLASH 1200C 2192F	DIELECTRIC 30kV+ Salt-spray safe
-----------------------------------	--	---