

PROTECTING ROLLING STOCK - TRACKSIDE INFRASTRUCTURE - MAINTENANCE DEPOTS

SRF FIRESLEEVE TAPE



WHAT IS IT?

SRF Firesleeve Tape is manufactured from 'E' glass fibre yarn, woven into a tape and coated with high-grade silicone elastomer rubber.

RAIL APPLICATIONS

- Terminating & sealing firesleeve on rolling stock
- Wrapping hydraulic & pneumatic hose joints
- Cable harness bundling & traction system protection
- Brake line lap-jointing & end sealing
- Depot maintenance wrap repairs
- Trackside cable & signalling line protection

STANDARD FORMAT

Widths available: **25, 50, 75, 100, 125 mm**
Method of supply: **30 m coils / cut lengths**

DEPOT & RETROFIT TIPS

Apply with 50% overlap for full coverage.
Use to terminate and seal firesleeve ends on rolling stock without line removal.
Glass locked edge for ready-cut lengths.

QUICK FACTS

Standard colour	Red Oxide
Continuous operating temp	250 C (482 F)
Molten splash resistance	Outstanding
Flame resistance	Very good
Abrasion resistance	Very good
Flexibility	Outstanding
Chemical resistance	Outstanding
Weather & UV resistance	Outstanding
Avg. dielectric strength	30 kV+
Wall thickness	3 - 4 mm

RAIL COMPLIANCE & STANDARDS

EN 45545-2	Railway fire protection standard
ISO 11925-2	Ignitability of products
IEC 60695-11-10	Classified HB and V0
UL94 V0 / V1 / V2	UL flammability rating
MSHA Certified	Mine Safety & Health Admin.
Made in Britain	Manufactured in Burnley, UK

CONTINUOUS 250C 482F	MOLTEN SPLASH 1200C 2192F	DIELECTRIC 30kV+ HV harness safe
-----------------------------------	--	---